



CAM & GROOVE COUPLING LINE

Type C Coupler

Aluminum Constructed Cam and Groove type C female coupler by hose shank. Also available in stainless steel and brass.



Hose Diameter	Part Number	Lbs./Each
3/4"	.75-C-ALUM-SP	0.26
1"	1.0-C-ALUM-SP	0.45
1-1/4"	1.25-C-ALUM-SP	0.70
1-1/2"	1.5-C-ALUM-SP	0.75
2"	2.0-C-ALUM-SP	1.04
2-1/2"	2.5-C-ALUM-SP	1.47
3"	3.0-C-ALUM-SP	2.04
4"	4.0-C-ALUM-SP	2.94
5"	5.0-C-ALUM-SP	3.37
6"	6.0-C-ALUM-SP	6.39
8"	8.0-C-ALUM-SP	13.00
3/4"	.75-C-BRASS-SP	0.46
1"	1.0-C-BRASS-SP	0.73
1-1/4"	1.25-C-BRASS-SP	1.15
1-1/2"	1.5-C-BRASS-SP	1.43
2"	2.0-C-BRASS-SP	1.91
2-1/2"	2.5-C-BRASS-SP	2.94
3"	3.0-C-BRASS-SP	3.58
4"	4.0-C-BRASS-SP	5.07
3/4"	.75-C-SS-SP	0.39
1	1.0-C-SS-SP	0.65
1-1/4"	1.25-C-SS-SP	1.02
1-1/5"	1.5-C-SS-SP	1.23
2	2.0-C-SS-SP	1.78
2-1/2"	2.5-C-SS-SP	2.77
3	3.0-C-SS-SP	3.4
4	4.0-C-SS-SP	5.89
5	5.0-C-SS-SP	7.25
6	6.0-C-SS-SP	11
2"	2.0-C-CS-SP	1.78
3"	3.0-C-CS-SP	3.88
4"	4.0-C-CS-SP	5.89