

# CAM & GROOVE COUPLING LINE

## Type D Coupler

Aluminum Constructed Cam and Groove type D female coupler by female NPT. Also available in stainless steel and brass.



Hose Diameter	Part Number	Lbs./Each
¾"	.75-D-ALUM-SP	0.26
1"	1.0-D-ALUM-SP	0.37
1-¼"	1.25-D-ALUM-SP	0.77
1-½"	1.5-D-ALUM-SP	0.80
2"	2.0-D-ALUM-SP	0.88
2-½"	2.5-D-ALUM-SP	1
3"	3.0-D-ALUM-SP	1.75
4"	4.0-D-ALUM-SP	2.51
5"	5.0-D-ALUM-SP	3.51
6"	6.0-D-ALUM-SP	5.31
8"	8.0-D-ALUM-SP	11
¾"	.75-D-BRASS-SP	0.44
1"	1.0-D-BRASS-SP	0.68
1-¼"	1.25-D-BRASS-SP	1.14
1-½"	1.5-D-BRASS-SP	1.32
2"	2.0-D-BRASS-SP	1.54
2-½"	2.5-D-BRASS-SP	1.98
3"	3.0-D-BRASS-SP	3.06
4"	4.0-D-BRASS-SP	4.96
¾"	.75-D-SS-SP	0.48
1"	1.0-D-SS-SP	0.81
1-¼"	1.25-D-SS-SP	1.44
1-½"	1.5-D-SS-SP	1.50
2"	2.0-D-SS-SP	1.82
2-½"	2.5-D-SS-SP	2.54
3"	3.0-D-SS-SP	3.24
4"	4.0-D-SS-SP	5.18
5"	5.0-D-SS-SP	8.35
6"	6.0-D-SS-SP	8.42