

TEX-GOLD

Premium Grade Skirtboard 60 Duro



General Properties and Applications

Ideal for conveyor belt systems, mounting pads, sealing strips and general industrial/construction use. Texcel's manufacturing process guarantees consistent gauge, width and quality, unlike extruded skirtboard. Packaged with three binding straps to keep rolls intact and prevent telescoping during shipping, storage and handling. Roll sizes are clearly marked for easy identification.

TECHNICAL DATA

Durometer	60 +/-5
Temperature	-25°F to +175°F
Composition	Abrasion-resistant SBR/GUM



Width	Gauge	Part Number	Ft./Roll	Lbs./Roll (avg.)
3"	1/4"	GOLD-8-3	50'	22
4"	1/4"	GOLD-8-4	50'	28
5"	1/4"	GOLD-8-5	50'	36
6"	1/4"	GOLD-8-6	50'	43
8"	1/4"	GOLD-8-8	50'	56
10"	1/4"	GOLD-8-10	50'	71
12"	1/4"	GOLD-8-12	50'	82
3"	3/8"	GOLD-12-3	50'	31
4"	3/8"	GOLD-12-4	50'	43
5"	3/8"	GOLD-12-5	50'	53
6"	3/8"	GOLD-12-6	50'	63
8"	3/8"	GOLD-12-8	50'	85
10"	3/8"	GOLD-12-10	50'	107
12"	3/8"	GOLD-12-12	50'	128
3"	1/2"	GOLD-16-3	50'	43
4"	1/2"	GOLD-16-4	50'	56
5"	1/2"	GOLD-16-5	50'	71
6"	1/2"	GOLD-16-6	50'	85

Width	Gauge	Part Number	Ft./Roll	Lbs./Roll (avg.)
8"	1/2"	GOLD-16-8	50'	113
10"	1/2"	GOLD-16-10	50'	141
12"	1/2"	GOLD-16-12	50'	170
3"	3/4"	GOLD-24-3	50'	63
6"	3/4"	GOLD-24-6	50'	127
8"	3/4"	GOLD-24-8	50'	170
9"	3/4"	GOLD-24-9	50'	198
10"	3/4"	GOLD-24-10	50'	215
12"	3/4"	GOLD-24-12	50'	255
3"	1"	GOLD-32-3	50'	85
4"	1"	GOLD-32-4	50'	113
6"	1"	GOLD-32-6	50'	170
8"	1"	GOLD-32-8	50'	227
10"	1"	GOLD-32-10	50'	283
12"	1"	GOLD-32-12	50'	340
8"	1-1/2"	GOLD-48-8	50'	300
10"	1-1/2"	GOLD-48-10	50'	375