


# TEX-CG-NEO

65 Duro Commodity-Grade Rubber



## General Properties and Applications

Commodity-grade elastomer sheet for basic applications where an economical rubber compound is needed. Ideally suited for stripping and applications where petroleum, chemical, weathering and ozone or oxidation is not required or present. Limited fluid-sealing capabilities.

## TECHNICAL DATA

Durometer	65 +/-5
Color	Black
Temperature	-25°F to +175°F
Tensile Strength	500 psi
Elongation	200%



Width	Gauge	Part Number	Ln. Ft./Roll	Sq. Yds./Roll	Lbs./Roll
36"	1/16"	CG-NEO-2-36	100'	33.3	146
	1/8"	CG-NEO-4-36	50'	16.7	146
	3/16"	CG-NEO-6-36	50'	16.7	220
	1/4"	CG-NEO-8-36	50'	16.7	293
	3/8"	CG-NEO-12-36	25'	8.3	220
	1/2"	CG-NEO-16-36	25'	8.3	293
	3/4"	CG-NEO-24-36	25'	8.3	439
	1"	CG-NEO-32-36	25'	8.3	585
48"	1/16"	CG-NEO-2-48	100'	44.4	195
	1/8"	CG-NEO-4-48	50'	22.2	195
	3/16"	CG-NEO-6-48	50'	22.2	293
	1/4"	CG-NEO-8-48	50'	22.2	390
	3/8"	CG-NEO-12-48	25'	11.1	293
	1/2"	CG-NEO-16-48	25'	11.1	390
	3/4"	CG-NEO-24-48	25'	11.1	585
	1"	CG-NEO-32-48	25'	11.1	780