




# MUNRO CONCENTRIC REDUCERS

Groove X Groove M7150 | Groove X Female NPT M7150F

Munro ductile iron grooved fittings are made to USA standards for consistent interchangeability with other major manufacturers. Pressure ratings conform to the pressure rating of installed couplings.



## TECHNICAL DATA

Composition Ductile iron, non-lead orange rust-inhibiting paint coating, ASTM A536, Grade 65-45-12

Nominal Size	Pipe OD	Description	E-E	Approx. Weight	Model Number
in/mm	in/mm		in/mm	lb/kg	
2 X 1 50 X 25	2.37 X 1.31 60 X 33	Groove X Female NPT	2.5 63.5	1 0.45	M7150FX2X1
2 X 1½ 50 X 40	2.37 X 1.90 60 X 48		2.5 63.5	1 0.45	M7150FX2X150
4 X 2 100 X 50	4.50 X 2.37 114 X 60		3 76	2 0.9	M7150FX4X2
6 X 4 150 X 100	6.62 X 4.50 168 X 114	Groove X Groove	4 102	6 2.72	M7150FX6X4
10 X 8 250 X 200	10.75 X 8.62 273 X 219		6 152	14 6.35	M7150X10X8
12 X 10 300 X 250	12.75 X 10.75 323 X 273		7 178	28 12.7	M7150X12X10
6 X 2 150 X 50	6.62 X 2.37 168 X 60		4 102	5 1.8	M7150X6X2
6 X 4 150 X 100	6.62 X 4.50 168 X 114		4 102	5 2.26	M7150X6X4
8 X 4 200 X 100	8.62 X 4.50 219 X 114	5 127	11 5	M7150X8X4	
8 X 6 200 X 150	8.62 X 6.62 219 X 168	5 127	9 4	M7150X8X6	