

TEX-ORANGE

40 Duro High Abrasion Skirtboard Rubber



TECHNICAL DATA

Durometer	40 +/-5
Temperature	-40°F to +178°F
Composition	Abrasion-resistant NR/IR
Abrasion Resistance	130 mm ³ @ 10n*
Color	Orange
Density	1.016 g/cm ³
Tensile Strength	3,150 psi
Elongation at Break	650%
Tear Resistance	631 psi

General Properties and Applications

TEX-ORANGE is a premium 40 Durometer skirtboard made for the most abusive conditions. Made of a specially compounded natural rubber, TEX-ORANGE offers the maximum protection in skirting and containment applications. With its high tensile strength and tear resistance, TEX-ORANGE is the most durable solution to insure that conveyor belt life is extended and overall system performance is maximized.

Benefits:

- Excellent abrasion resistance
- Enhanced performance over commercial grade compounds
- Protects the conveyor belt thereby minimizing downtime



Width	Gauge	# Part Number	Ft./Roll	Lbs./Roll (avg.)
4"	1/4"	ORANGE-8-4	50'	22
6"	1/4"	ORANGE-8-6	50'	33
8"	1/4"	ORANGE-8-8	50'	44
10"	1/4"	ORANGE-8-10	50'	55
12"	1/4"	ORANGE-8-12	50'	66
48"	1/4"	ORANGE-8-48	50'	264
4"	3/8"	ORANGE-12-4	50'	33
6"	3/8"	ORANGE-12-6	50'	50
8"	3/8"	ORANGE-12-8	50'	66
10"	3/8"	ORANGE-12-10	50'	84
12"	3/8"	ORANGE-12-12	50'	100
48"	3/8"	ORANGE-12-48	50'	401
4"	1/2"	ORANGE-16-4	50'	44
6"	1/2"	ORANGE-16-6	50'	66

Width	Gauge	# Part Number	Ft./Roll	Lbs./Roll (avg.)
8"	1/2"	ORANGE-16-8	50'	88
10"	1/2"	ORANGE-16-10	50'	110
12"	1/2"	ORANGE-16-12	50'	132
48"	1/2"	ORANGE-16-48	50'	528
6"	3/4"	ORANGE-24-6	50'	99
8"	3/4"	ORANGE-24-8	50'	132
10"	3/4"	ORANGE-24-10	50'	165
12"	3/4"	ORANGE-24-12	50'	198
48"	3/4"	ORANGE-24-48	50'	191
6"	1"	ORANGE-32-6	50'	132
8"	1"	ORANGE-32-8	50'	176
10"	1"	ORANGE-32-10	50'	220
12"	1"	ORANGE-32-12	50'	264
48"	1"	ORANGE-32-48	50'	1055

*Independent 3rd party test showed Texcel had best in class results