



 **TEXCEL**

Tex FKM



Premium Grade Fluorocarbon - elastomers (Type A) Sheet

Type A (66%+ Fluorine) cinnamon scented sheet rubber conform to MIL Spec R-83248 Type II Class I. Tex-FKM is used in applications requiring outstanding resistance to heat and/or chemical solutions. Fluorocarbon-elastomer Type A exhibits low compression set, but is not resistant to flex fuels containing high levels of alcohol or MTBE (reformulated gasoline/oxygenated). In some applications, rubber parts are stressed by accidental temperature surges or elevated operating temperatures designed to increase productivity. For these applications, FKM is an excellent alternative to Neoprene, EPDM or other elastomers.

Features and Benefits include:

- Offered by the Full Roll or Linear Yard
- Extra smooth surface

Technical Data

Part Number	FKM-2
Durometer	75 +/-5
Color	Black, smooth, cinnamon scented
Tensile Strength	1,000 psi
Elongation	225%
Safety Factor	4:1
Temperature	-20°F to +350°F
MIL Spec	R-83248 Type II Class I

Width (in.)	Gauge (in.)	Ln Ft / Roll	Sq Yds / Roll	Lbs / Roll
48"	1/16"	51'	22.67	124
	1/8"	51'	22.67	247
	3/16"	51'	22.67	371
	1/4"	51'	22.67	494
	3/8"	27'	12	371
	1/2"	27'	12	494



- Servicing the industry for over 25 years.
- Leading-Edge Technology
- No Surprises...Guaranteed!

- 100% Same-Day Shipping...Guaranteed!
- 99.998% Error-Free Rate
- Large Inventories



DISTRIBUTED BY: