

Gamma-BULK CEMENT DISCHARGE HOSE



General Properties and Applications

Abrasion resistant tube and cover fabricated with the highest quality elastomer compounds for maximum performance. Softwall hose used in transfer of dry materials and slurries. Ideal for dry cement, pebble lime and other abrasive media.



Technical Data

Construction	Type "D"
Tube	Black, Abrasion-resistant NB/SBR, Static dissipating materials
Cover	Black, Abrasion-resistant NR/SBR
Temperature	-40°F to +180°F
Safety Factor	4:1
Reinforcement	High tensile strength tire cord plies (static ground wire)
Branding	Unbranded

Inside Diameter (in.)	Outside Diameter (in.)	Part Number	Tube Gauge (in.)	Standard Length (ft.)	Working Pressure (psi)	Number of Plies	Weight / Foot (lbs.)
4"	4-7/16"	GBU75S1-4-4	1/8"	100'	75	2	1.72
	4-5/8"	GBU75S1-4-6	3/16"	100'		2	2.27
	4-51/64"	GBU75S1-4-8	1/4"	100'		2	2.49
5"	5-15/32"	GBU75S1-5-4	1/8"	100'	75	2	3.09
	5-5/8"	GBU75S1-5-6	3/16"	100'		2	3.24
	5-51/64"	GBU75S1-5-8	1/4"	100'		2	3.99



Cut Lengths Available



Tex-TIP:

Tex-BULK is also excellent as a water discharge hose when abrasive materials are present in the water.

