

Gamma-COMM DISCHARGE BLACK COMMODITY DISCHARGE HOSE



General Properties and Applications

Softwall hose designed with a high abrasion resistant tube. Ideal for application where discharging abrasive media is required.

Technical Data

Construction	Type "D"
Tube	1/4" Black, Abrasion-resistant
Cover	Black, Abrasion-resistant
Temperature	-40°F to +180°F
Safety Factor	4:1
Reinforcement	High tensile strength tire cord plies
Branding	WET-DRY BULK COMMODITY DISCHARGE HOSE STATIC CONDUCTIVE TUBE XXX PSI W.P. (White lay line with black letters)



Inside Diameter (in.)	Outside Diameter (in.)	Part Number	Tube Gauge (in.)	Standard Length (ft.)	Working Pressure (psi)	Number of Plies	Weight / Foot (lbs.)
2"	2-45/64"	GCOMM-D-B1-2.0	3/16"	100'	150	2	1.51
2-1/2"	3-13/64"	GCOMM-D-B1-2.5	3/16"	100'	125	2	1.82
3"	3-46/64"	GCOMM-D-B1-3.0	3/16"	100'	125	2	2.20
4"	4-45/64"	GCOMM-D-B1-4.0	3/16"	100'	100	2	2.79
5"	5-45/64"	GCOMM-D-B1-5.0	1/4"	100'	75	2	3.40
6"	6-45/64"	GCOMM-D-B1-6.0	1/4"	100'	75	2	4.06



Cut Lengths Available



Tex-TIP:

Periodically rotating hoses 90 degrees in abrasive applications ensures even tube wear, dramatically increasing hose life and reducing costly downtime.



Tel 800.231.7116

Fax 800.759.4673

www.texcelrubber.com

