

Gamma- Flex BLACK TANK FLEX TANK TRUCK HOSE



General Properties and Applications

A world-class hose for tank truck, in-plant and oil field loading operations requiring a strong yet flexible hose. Exceptional flexibility (one to one ration) for ease of handling.

Technical Data

Construction	Type "E"
Tube	Black, Nitrile, 55% aromatics (ORS)
Cover	Black, Neoprene (Corrugated)
Safety Factor	4:1
Temperature	-40°F to +180°F
Reinforcement	High tensile strength tire cord plies, Helix Wire
Ends	Soft cuffs on 200ft lengths
Branding	<i>Gamma Flex Series</i> FLEXIBLE PETROLEUM TANK TRUCK 150 PSI WP (Red lay line with black letters)



Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius (in.)	Weight / Foot (lbs.)
1-1/2"	GTA15F1-1.5	1-63/64"	100'/200'	150	30	1.5"	0.77
2"	GTA15F1-2.0	2-15/32"	100'/200'	150	30	2"	1.02
2-1/2"	GTA15F1-2.5	3"	100'/200'	150	30	2.5"	1.31
3"	GTA15F1-3.0	3-1/2"	100'/200'	150	30	3"	1.60
4"	GTA15F1-4.0	4-9/16"	100'/200'	150	30	4"	2.55
5"	GTA15F1-5.0	5-46/64"	100'/200'	150	30	6"	3.86
6"	GTA15F1-6.0	6-3/4"	100'	150	25	8"	4.17
8"	GTA15C1-8.0	8-13/16"	100'	80	25	10"	6.02



EXCEPTIONAL FLEXIBILITY



Cut Lengths Available

