

Gamma-TANK 300

CORRUGATED

CORRUGATED 300PSI TANK TRUCK HOSE



General Properties and Applications


TANK 300 is designed for offshore drilling and other demanding applications where longer lengths and fewer connections are desired. Premium hose design for superior performance and higher working pressure in tough environments. Cover withstands exposure to weather, saltwater, sunlight and oil.

Technical Data

Construction	Type "E"
Tube	Black, Nitrile, 55% Aromatics (ORS)
Cover	Black, Neoprene (Corrugated)
Temperature Range	- 40°F to +180°F
Reinforcement	High tensile strength synthetic plies, Helix wires
Ends	Soft cuffs on 200ft lengths
Branding	TANK TRUCK HOSE 300 PSI WP (Red layline with black letters)



Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius (in.)	Weight / Foot (lbs.)
2"	GTA30C1-2.0	2-1/2"	100'/200'	300	30	4"	1.06
3"	GTA30C1-3.0	3-39/64"	100'/200'	300	30	7"	1.72
4"	GTA30C1-4.0	4-23/32"	100'/200'	300	30	10"	2.72
6"	GTA30C1-6.0	6-60/64"	100'	300	30	20"	5.41



Cut Lengths Available

