

Gamma-WIRE CRETE CONCRETE, PLASTER AND GROUT HOSE

General Properties and Applications

For use in plaster, grout and concrete placement applications with high head pressure and where a wire reinforced hose is desired.

Technical Data

Construction	Type "D"
Tube	Black, Wear resistant NR/SBR blend
Cover	Black, wear and weather resistant NR/SBR blend
Temperature Range	-40°F to +158°F
Reinforcement	Multiple steel wire plies
Specifications	Per CPMA Standards
Safety Factor	2:1 (per CPMA Standards)
Branding	Unbranded

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)/(bar)	Burst Pressure (psi)	Weight / Foot (lbs.)
1-1/2"	GWC100S1-1.5	2-1/8"	100'	1450 / 100	3000	1.35
2"	GWC100S1-2.0	2-5/8"	100'	1450 / 100	3000	1.74
2-1/2"	GWC100S1-2.5	3-1/8"	100'	1450 / 100	3000	2.58
3"	GWC85S1-3.0	3-7/8"	100'	1230 / 85	2800	4.05
4"	GWC85S1-4.0	4-7/8"	50' / 100'	1230 / 85	2800	5.95
5"	GWC85S1-5.0	6-9/64"	12-1/2'	1230 / 85	2800	7.44

