

Sigma-ECONO CLEAR PVC ECONOMICAL CLEAR PVC SUCTION HOSE



General Properties and Applications

Heavy duty yet economical construction for great durability. Clear PVC allows visual confirmation of product flow. Used for water and pumping media under suction or pressure.

Technical Data

Construction	Type "G"
Tube and Cover	Clear, PVC (Smooth)
Temperature	-4°F to +150°F
Safety Factor	3:1
Reinforcement	White, Tough vinyl helix
Branding	Sigma Series ECON CLEAR - <ID> - LOT
Compare to	112 CL / Sp-115

New **SIGMA**
Plastic Series

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius (in.)	Weight / Foot (lbs.)
1-1/2"	SPVC-CE-1.5	1.75"	100'	70	29	4"	0.37
2"	SPVC-CE-2.0	2.28"	100'	65	29	5"	0.61
2-1/2"	SPVC-CE-2.5	2.83"	100'	65	29	6"	0.87
3"	SPVC-CE-3.0	3.35"	100'	55	29	8"	1.05
4"	SPVC-CE-4.0	4.45"	100'	50	29	10"	1.80

✓ Sold in Standard Lengths Only

