

# Sigma-POLY BLUE


## BLUE PVC DISCHARGE HOSE



### General Properties and Applications

Premium quality, lightweight lay flat PVC hose that is economical and easy to handle. Excellent for pump discharge applications.

### Technical Data

Construction	Type "H"
Tube and Cover	Blue, Homogenous PVC
Temperature Range	-10°F to +120°F
Safety Factor	3:1
Reinforcement	High tensile polyester yarn
Branding	 <b>TEXCEL</b> WATER DISCHARGE (White letters)

Inside Diameter (in.)	Part Number	Standard Length (ft.)	Working Pressure (psi)	Weight / Foot (lbs.)
1"	SPVC-PB-1.0-300	300'	90	0.103
1-1/4"	SPVC-PB-1.25-300	300'	85	0.117
1-1/2"	SPVC-PB-1.5-300	300'	70	0.140
2"	SPVC-PB-2.0-300	300'	64	0.183
2-1/2"	SPVC-PB-2.5-300	300'	60	0.257
3"	SPVC-PB-3.0-300	300'	55	0.307
4"	SPVC-PB-4.0-300	300'	55	0.360
5"	SPVC-PB-5.0-300	300'	42	0.640
6"	SPVC-PB-6.0-300	300'	42	0.733
8"	SPVC-PB-8.0-300	300'	42	1.210

✓ Sold in Standard Lengths Only

① Combine Sigma-POLY BLUE with any other Texcel products for Prepaid Freight on shipments of \$3,000.



#### Tex-TIP:

Texcel's very competitive pricing on PVC discharge hose helps your customer's bottom line by allowing them to substitute this hose when possible for more expensive hoses.

