

# Tex-STEAM

## WIRE STEAM HOSE



### General Properties and Applications

Rugged wire-braid steam hose recommended for saturated and super heated steam applications in chemical plants, shipyards and industrial plants.

### Technical Data

Construction	Type "B"
Tube	Black, heat resistant EPDM
Cover	Black, EPDM (pinpricked)
Temperature	-40°F to +450°F
Safety Factor	10:1
Reinforcement	2 braids high tensile steel
Branding	2 WIRE BRAID STEAM HOSE - 250 PSI WP - 450°F - DRAIN AFTER USE (Continuous impression embossed on hose)

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Bend Radius (in.)	Weight / Foot (lbs.)
1/2"	STEAM-.50	15/16"	50'	250	3"	0.40
3/4"	STEAM-.75	1-1/4"	50'	250	4"	0.56
1"	STEAM-1.0	1-1/2"	50'	250	6"	0.72
2"	STEAM-2.0	2-11/16"	50'	250	12"	1.51

✓ Sold in Standard Lengths Only.

- ① Drain the hose after each use for maximum hose life.
- ① Do not alternate use between steam and water.
- ① Consult the coupling manufacturer for the proper fitting recommendation and coupling procedure.



#### Tex-TIP:

Only couplings approved for steam use by the coupling manufacturer should be used. The couplings should be inspected and tightened prior to each use to ensure safety.

