

Tex-BLAST

SAND BLAST HOSE



General Properties and Applications

The industry's premium sandblast hose is constructed with high quality elastomers for long "shift life." Engineered to provide superior flexibility, length stability and excellent abrasion resistance. Used with grit, aluminum oxide, glass beads, etc. and is ideal for rugged use in shipyards and construction sites.

Technical Data

Construction	Type "D"
Tube	Black, SBR/GUM, wear-resistant, static dissipating
Cover	Black, SBR (Pinpricked)
Temperature Range	-40°F to +190°F
Safety Factor	4:1
Reinforcement	High tensile strength synthetic tire cord plies
Branding	PREMIUM GRADE BLAST HOSE 150 PSI WP (Yellow line with black letters)

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Fabric Plies	Weight / Foot (lbs.)
1/2"	BLAST-.50	1-1/8"	50'	150	2	0.40
3/4"	BLAST-.75	1-1/2"	50'	150	4	0.57
1"	BLAST-1.0	1-7/8"	50'	150	4	0.94
1-1/4"	BLAST-1.25	2-1/8"	50'	150	4	1.18
1-1/2"	BLAST-1.50	2-3/8"	50'	150	4	1.35

✓ Sold in Standard Lengths Only



Tex-TIP:

Periodically rotating hoses 90 degrees in abrasive applications ensures even tube wear, dramatically increasing hose life and reducing costly downtime.

