

Tex-SBR CI

NYLON INSERTED SBR SHEET



General Properties and Applications

SBR rubber with square woven 3.4 ounce nylon plies for durability in dynamic applications requiring extra strength. Excellent stretch, creep, and tear resistance. Our exclusive post-cure process provides a smooth and clean finish free of talc, a must for PSA applications.

Technical Data

Durometer	60 +/-5
Color	Black
Temperature Range	-20°F to +170°F
Fabric Type	3.4 ounce nylon
Continuous Lay Line	Includes style, durometer, and lot code
ASTM Line Call Out	D2000-M2-AA603-A13-B33-EA14

Width (in.)	Gauge (in.)	Part Number	Ln Ft/ Roll	Fabric Plies	Lbs/ Roll
48"	1/16"	CI-2	150'	1	295
	1/8"	CI-4	75'	2	295
	3/16"	CI-6	50'	3	295
	1/4"	CI-8	37.5'	4	295

- ① Talc-free surface eliminates the need to clean the sheet rubber and is ideal for PSA applications.
- ① Certificates of Conformance indicating production date and lot code are available on request at the time of order.



Tex-TIP:

Tex-SBR CI is an excellent sheet for municipalities, water plants and other facilities where a strong, durable and economical sheet is required.

