

# Tex-CRETE

## CONCRETE, PLASTER AND GROUT HOSE



### General Properties and Applications

Texcel's exclusive design provides the ultimate combination of handling ease, abuse resistance and long service life required for plaster, grout and concrete placement applications. Ideal for concrete jetting applications.

### Technical Data

Construction	Type "D"
Tube	Black, Wear resistant GUM/SBR blend
Cover	Black, SBR - cut and gouge resistant
Temperature Range	-40°F to +200°F
Safety Factor	2:1 <b>(Per CPMA Standards)</b>
Reinforcement	Multiple plies of high tensile strength tire cord plies
Branding	Concrete Placement Hose – Fabric X" XXXXPSI (XX BAR) WP XXLBS/FT (F.W.C.) Meets or Exceeds CPMA 27-200 (Red layline with Black letters)

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)/bar	Burst Pressure (psi)/bar	Bend Radius (in.)	Weight / Foot (lbs.)	Fabric Plies
1-1/4"	CRETE-1.25	2"	100'	1230/85	2650/170	8"	0.86	4
1-1/2"	CRETE-1.5	2-3/16"	100'	1230/85	2650/170	10"	0.92	4
2"	CRETE-2.0	2-49/64"	100'	1230/85	2650/170	12"	1.45	6
2-1/2"	CRETE-2.5	3-11/32	100'	1230/85	2650/170	14"	1.71	6
3"	CRETE-3.0	4"	100'	825/55	1650/110	15"	2.40	6
3-1/2"	CRETE-3.5	4-31/64"	100"	825/55	1650/110	16"	3.07	8
4"	CRETE-4.0-100	5-5/32"	100'	825/55	1650/110	18"	4.06	8
	CRETE-4.0-12.5	5-5/32"	12.5'	825/55	1650/110	18"	4.06	8
4-1/2"	CRETE-4.5-100	5-19/32"	50'	825/55	1650/110	21"	4.22	8
	CRETE-4.5-12.5	5-19/32"	12.5'	825/55	1650/110	21"	4.22	8
5"	CRETE-5.0	6-19/64"	100'	825/55	1650/110	24"	5.60	8
6"	CRETE-6.0	7-21/64"	100	825/55	1650/110	30"	6.80	10



**Cut Lengths Available**

#### Tex-TIP:

Texcel stocks 4-1/2" x 12.5' straight lengths for concrete pumpers who want a durable, long-lasting boom hose that is straight with no "banana" effect.

