

# Tex-FLO HD

## HEAVY DUTY 4-PLY WATER DISCHARGE



### General Properties and Applications

Soft-wall design gives similar performance to a lay flat hose but with increased abrasion resistance and tensile strength. FLO HD is made of premium quality SBR/EPDM blend for maximum weather resistance and life in abusive service.

### Technical Data

Construction	Type "D"
Tube	Black, SBR/EPDM blend
Cover	Black, SBR/EPDM blend
Temperature	-40°F to +190°F
Safety Factor	3:1
Reinforcement	High tensile strength tire cord plies
Branding	Unbranded

► **Medium Duty Discharge Hose: See Tex-FLO MD**

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Fabric Plies	Working Pressure (psi)	Weight / Foot (lbs.)
1-1/2"	FLO-4HD-1.5	1-57/64"	100'	4	250	0.55
2"	FLO-4HD-2.0	2-25/64"	100'	4	250	1.00
2-1/2"	FLO-4HD-2.5	2-57/64"	100'	4	250	1.33
3"	FLO-4HD-3.0	3-25/64"	100'	4	250	1.58
4"	FLO-4HD-4.0	4-7/16"	100'	4	200	2.15
4-1/2"	FLO-4HD-4.5	4-15/16"	100'	4	200	2.40
5"	FLO-4HD-5.0	5-7/16"	100'	4	200	2.70
6"	FLO-4HD-6.0	6-7/16"	100'	4	200	3.25
8"	FLO-4HD-8.0	8-15/32"	100'	4	150	4.50
10"	FLO-4HD-10.0	10-17/32"	100'	4	150	5.50
12"	FLO-4HD-12.0	12-17/32"	100'	4	150	8.00



**Cut Lengths Available**

