

# Tex-FLO MD

## MEDIUM DUTY 2-PLY WATER DISCHARGE



### General Properties and Applications

Soft-wall design gives similar performance to a lay flat hose but with increased abrasion resistance and tensile strength. FLO MD is made of premium quality SBR/EPDM blend for maximum weather resistance and life in abusive service.

### Technical Data

Construction	Type "D"
Tube	Black, SBR/EPDM blend
Cover	Black, SBR/EPDM blend
Temperature	-40°F to +180°F
Safety Factor	3:1
Reinforcement	High tensile tire cord plies
Branding	Unbranded

► Heavy Duty Discharge Hose: See Tex-FLO HD

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Fabric Plies	Working Pressure (psi)	Weight / Foot (lbs.)
1-1/2"	FLO-2MD-1.5	1-25/32"	100'	2	150	0.44
2"	FLO-2MD-2.0	2-9/32"	100'	2	150	0.62
2-1/2"	FLO-2MD-2.5	2-25/32"	100'	2	150	0.75
3"	FLO-2MD-3.0	3-9/32"	100'	2	150	0.95
4"	FLO-2MD-4.0	4-5/16"	100'	2	150	1.25
6"	FLO-2MD-6.0	6-5/16"	100'	2	100	2.68
8"	FLO-2MD-8.0	8-23/64"	100'	2	100	3.77
10"	FLO-2MD-10.0	10-27/64"	100'	2	80	5.00



**Cut Lengths Available**



#### Tex-TIP:

Most hose failures are caused by external or handling factors and occur within two feet of the couplings. Often rerouting hoses or protecting them from abuse dramatically increases service life.

