

Tex-GOLD

PREMIUM GRADE SKIRTBOARD



General Properties and Applications

Ideal for conveyor belt systems, mounting pads, sealing strips and general industrial/construction use. Texcel's manufacturing process guarantees consistent gauge, width and quality unlike extruded products. Packaged with three binding straps to keep rolls in tact and prevent telescoping during shipping, storage and handling. Roll sizes are clearly marked for easy identification.

Technical Data

Durometer	60 +/-5
Tensile Strength	1,200
Temperature Range	-25°F to +175°F
Elongation	350%
Composition	Abrasion-resistant SBR/GUM
ASTM Call Out	D2000-M2-AA608-BB33-EA14



Gauge x Width (in.) (in.)	Part Number	Feet / Roll	Lbs / Roll (avg.)
1/4" x 3"	GOLD-8-3	50'	22
1/4" x 4"	GOLD-8-4	50'	28
1/4" x 5"	GOLD-8-5	50'	36
1/4" x 6"	GOLD-8-6	50'	43
1/4" x 8"	GOLD-8-8	50'	56
1/4" x 10"	GOLD-8-10	50'	71
1/4" x 12"	GOLD-8-12	50'	82
3/8" x 3"	GOLD-12-3	50'	31
3/8" x 4"	GOLD-12-4	50'	43
3/8" x 5"	GOLD-12-5	50'	53
3/8" x 6"	GOLD-12-6	50'	63
3/8" x 8"	GOLD-12-8	50'	85
3/8" x 10"	GOLD-12-10	50'	107
3/8" x 12"	GOLD-12-12	50'	128
1/2" x 3"	GOLD-16-3	50'	43
1/2" x 4"	GOLD-16-4	50'	56
1/2" x 5"	GOLD-16-5	50'	71
1/2" x 6"	GOLD-16-6	50'	85
1/2" x 8"	GOLD-16-8	50'	113
1/2" x 10"	GOLD-16-10	50'	141
1/2" x 12"	GOLD-16-12	50'	170

Gauge x Width (in.) (in.)	Part Number	Feet / Roll	Lbs / Roll (avg.)
3/4" x 3"	GOLD-24-3	50'	63
3/4" x 6"	GOLD-24-6	50'	127
3/4" x 8"	GOLD-24-8	50'	170
3/4" x 9"	GOLD-24-9	50'	198
3/4" x 10"	GOLD-24-10	50'	215
3/4" x 12"	GOLD-24-12	50'	255
1" x 3"	GOLD-32-3	50'	85
1" x 4"	GOLD-32-4	50'	113
1" x 6"	GOLD-32-6	50'	170
1" x 8"	GOLD-32-8	50'	227
1" x 10"	GOLD-32-10	50'	283
1" x 12"	GOLD-32-12	50'	340
1-1/2" x 10"	GOLD-48-10	50'	375

① Tex-GOLD can be combined with Tex-TUFF, Tex-WIPER, Tex-BEVEL and Tex-PROTECT to achieve maximum price breaks.

① Combine Tex-GOLD with any other Texcel products for Prepaid Freight on shipments of \$2,000 or 2,000 lbs.

