

Tex-GS



GENERAL SERVICE AIR WATER HOSE

General Properties and Applications

General service hose for a wide variety of air and water applications. Specially designed for excellent sunlight and ozone resistance.

Technical Data

Construction	Type "A"
Tube	Black, EPDM
Cover	Red or Black, EPDM
Temperature	-20°F to +180°F
Reinforcement	One or two spiral polyester cords
Branding	TEXCEL GS250 GENERAL SERVICE AIR AND WATER SIZE – WP – LOT CODE (White letters)
Packaging	Reels or coils

Inside Diameter (in.)	Package Type	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Weight / Package (lbs.)
1/4"	Reel	GS-4-R250-600R	15/32"	600'	250	72.8
1/4"	Coil	GS-4-C250-200R	15/32"	200'	250	25.0
5/16"	Reel	GS-5-R250-600R	9/16"	600'	250	89.0
3/8"	Reel	GS-6-R250-600R	21/32"	600'	250	92.6
3/8"	Coil	GS-6-C250-200R	21/32"	200'	250	37.5
1/2"	Reel	GS-8-R250-600R	25/32"	600'	250	137.8
1/2"	Coil	GS-8-C250-200R	25/32"	200'	250	43.3
5/8"	Reel	GS-10-R250-600R	1"	600'	250	190.3
3/4"	Reel	GS-12-R250-600R	1-3/16"	600'	250	242.5
	Coil	GS-12-C250-50R	1-3/16"	50'	250	18.8
	Coil	GS-12-C250-200R	1-3/16"	200'	250	75.0
1"	Reel	GS-16-R200-400R	1-3/8"	400'	200	226.0
	Coil	GS-16-C200-50R	1-3/8"	50'	200	225.35

✓ Sold in Standard Lengths Only



Tex-TIP:

Tex-GS is available in both coils and reels in select sizes to provide you with the most options. Texcel also offers pre-assembled Contractor's Air Assemblies for same-day shipments.

