

# Tex-GS2 Assembly

## CONTRACTOR'S AIR ASSEMBLY



### General Properties and Applications

A tough, heavy duty, abrasion and ozone resistant general service hose coupled with plated universal fittings secured with two galvanized steel Band-It® band on each end.

### Technical Data

Construction	Type "A"
Tube	Black, EPDM
Cover	Red or Black, EPDM
Temperature	-20°F to +180°F
Reinforcement	One or two spiral polyester cords
Branding	TEXCEL GS250 GENERAL SERVICE AIR AND WATER SIZE – WP – LOT CODE (White letters)
Couplings	Plated universal fittings with two galvanized steel Band-It® band on each end
Packaging	Shrink-wrapped coils

Contractor's Air Assembly	Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Weight / Foot (lbs.)
50' Air Hose with Crow's Feet	3/4"	CON-24-250-50R2	1-3/16"	50'	250	0.39
	1"	CON-32-200-50R2	1-3/8"	50'	200	0.56



✓

**Tex-TIP:**

Save time, money and labor expense on your general service hose assemblies by sourcing them from Texcel. Assemblies are ready made for same-day shipments.

