

Tex-GUM

PURE GUM SHEET



General Properties and Applications

Soft, highly abrasion resistant Natural Rubber sheet used when resiliency, wear and cushioning are required. Not recommended for ozone or oil resistance.

Technical Data

Durometer	40 +/-5
Color	Tan
Tensile Strength	2,500 psi
Elongation	600%
Temperature Range	-20°F to +160°F
Continuous Lay Line	Includes style, durometer, and lot code
ASTM Line Call Out	D2000-M2-AA4071-A13-B33-F17

Width (in.)	Gauge (in.)	Part Number	Ln Ft/ Roll	Sq Yds/ Roll	Lbs/ Roll
36"	1/8"	GUM-4-36	50'	16.6	103
	3/16"	GUM-6-36	50'	16.6	154
	1/4"	GUM-8-36	50'	16.6	205
	3/8"	GUM-12-36	50'	16.6	307
	1/2"	GUM-16-36	25'	8.3	205
	3/4"	GUM-24-36	25'	8.3	307
	1"	GUM-32-36	25'	8.3	410
48"	1/8"	GUM-4-48	50'	16.6	137
	1/4"	GUM-8-48	50'	16.6	273
	3/8"	GUM-12-48	50'	16.6	410
	1/2"	GUM-16-48	25'	8.3	273



Tex-TIP:

Tex-GUM is compounded with high quality Natural Rubber for outstanding performance. It is ideal for boots on concrete trucks

