

Tex-KING

WIRE AIR HOSE



General Properties and Applications

High quality, heavy-duty wire reinforced hose for high pressures and abusive applications. Product users prefer this premium quality hose for its high performance record under the most abusive conditions. The ideal "Bull Hose" for heavy construction, mining and road building service. Also used for high pressure water.

Technical Data

Construction	Type "B"
Tube	Black, Nitrile blend
Cover	Yellow, EPDM / SBR
Temperature	-40°F to +212°F Intermittent to 250°F
Safety Factor	4:1
Reinforcement	Steel wire plies
Branding	STEEL AIR HOSE XXXPSI MAX WP (Embossed)

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Weight / Foot (lbs.)
1/2"	KING-0.5	15/16"	100'	1,000	0.36
3/4"	KING-.75	1-1/4"	100'	800	0.61
1"	KING-1.0	1-1/2"	100'	800	0.78
1-1/2"	KING-1.5	2-7/64"	100'	600	1.31
2"	KING-2.0	2-19/32"	100'	600	1.76
2-1/2"	KING-2.5	3-11/64"	100'	600	2.34
3"	KING-3.0	3-45/64"	100'	600	3.34
4"	KING-4.0	4-13/16"	100'	400	4.55



Tex-TIP:

Heavy Duty Air Hose is also known as "Bull Hose", "Rockdrill Hose" or "Manifold Supply Line." These terms are used for large diameter, usually 2" or above, tough hose for quarries, mining or construction.

