

Tex-MOR

60 DURO MODERATE OIL RESISTANT SHEET



General Properties and Applications

Commercial grade sheet rubber used for a wide variety of gasket, sealing, cushioning, and weather stripping applications where medium oil resistance is required. Our exclusive post-cure process provides a smooth and clean finish free of talc, a must for PSA applications.

Technical Data

Durometer	60 +/-5
Color	Black
Temperature Range	-20°F to +190°F
ASTM Line Call Out	D2000-M2-AA603-A13-B33-EA14

Width (in.)	Gauge (in.)	Part Number	Ln Ft/ Roll	Sq Yds/ Roll	Lbs/ Roll
36"	1/16"	MOR-2-36	50'	16.7	71
	3/32"	MOR-3-36	50'	16.7	106
	1/8"	MOR-4-36	50'	16.7	142
	3/16"	MOR-6-36	50'	16.7	213
	1/4"	MOR-8-36	50'	16.7	284
	3/8"	MOR-12-36	50'	16.7	426
	1/2"	MOR-16-36	50'	16.7	568
	3/4"	MOR-24-36	30'	10	511
	1"	MOR-32-36	30'	10	681
48"	1/16"	MOR-2-48	50'	22.2	95
	1/8"	MOR-4-48	50'	22.2	189
	3/16"	MOR-6-48	50'	22.2	284
	1/4"	MOR-8-48	50'	22.2	378
	3/8"	MOR-12-48	50'	22.2	568
	1/2"	MOR-16-48	50'	22.2	757
	3/4"	MOR-24-48	30'	13.3	681
	1"	MOR-32-48	30'	13.3	908

- ① Talc-free surface eliminates the need to clean the sheet rubber and is ideal for PSA applications.
- ① Certificates of Conformance indicating production date and lot code are available on request at the time of order.



Tex-TIP:

Gasket fabricators like Tex-MOR because its longer roll lengths increase yield. In addition, the material cuts well and is easy to handle.

