



# Tex-OIL

## PETROLEUM DISCHARGE HOSE

### General Properties and Applications

Softwall oil discharge hose designed for use on trucks, docks and barges where a light, easily handled hose is desired and when the application does not have to resist a vacuum. Also used in oil field liquid mud applications.

### Technical Data

Construction	Type "D"
Tube	Black, Nitrile, 50% aromatics (ORS)
Cover	Black, Neoprene
Plies	Four (4) High tensile tire cord plies
Temperature Range	-40°F to +190°F
Safety Factor	4:1
Reinforcement	High tensile strength tire cord plies
Static Grounding	Braided Copper Wire runs length of hose
Branding	Sizes 1-1/2" thru 3": PETROLEUM TRANSFER / DISCHARGE 200 PSI WP (Red with black letters) Sizes 4" thru 8": Unbranded
Specifications	Meets U.S.C.G. and RMA Class II Requirements
Couplings	Full fabrication services available, with swaging and USCG Certifications available through 8" ID.

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Weight / Foot (lbs.)
1-1/2"	OIL-D-1.5	2"	100'	200	0.90
2"	OIL-D-2.0	2-1/2"	100'	200	1.42
3"	OIL-D-3.0	3-1/2"	100'	200	1.86
4"	OIL-D-4.0	4-17/32"	100'	200	2.68
6"	OIL-D-6.0	6-27/32"	100'	200	5.89
8"	OIL-D-8.0	9-1/8"	100'	200	7.86



#### Tex-TIP:

The U.S. Coast Guard requires all hose assemblies for transfer of petroleum products around waterways to be pressure tested, certified and marked prior to use. Texcel offers this service on assemblies.

