

Tex-SUPER FRAC FRAC TANK HOSE



General Properties and Applications

Texcel's exclusive design for frac tank service, oilfield suction and water applications. Corrugated cover allows maximum flexibility. Ideal for handling salt and fresh water, tank bottoms, crude oil, drilling mud, and mild solutions of hydrochloric acids. Short lengths with soft cuffs on each end for easy coupling.

Not recommended for refined petroleum products.

Technical Data

Construction	Type "E"
Tube	Black, Specially compounded elastomer—Low Oil Swell
Cover	Black, SBR/Nitrile blend compounded for oil and ozone resistance (Corrugated)
Temperature	-40°F to +190°F
Safety Factor	3:1
Reinforcement	High tensile synthetic plies with wire helix
Ends	Soft cuffs
Branding	PREMIUM FRAC TANK HOSE NOT FOR REFINED FUELS 100 PSI WP (Gray with black letters)

Inside Diameter (in.)	Part Number	Outside Diameter (in.)	Standard Length (ft.)	Working Pressure (psi)	Vacuum (in./HG)	Weight /Length (lbs.)	Soft Cuff Length (in.)
8"	FRAC-8.0-40	8-47/64"	40"	100	25	23.0	5-8/64"
	FRAC-8.0-48		48"			27.0	
	FRAC-8.0-60		60"			33.0	



✓

Tex-TIP:
Tex-SUPER FRAC can also be used for plant waste, machine shop fluids, sewage and other applications requiring medium oil resistance in an easy to handle suction hose.

