

Tex-TUFF

CHUTE LINING SKIRTBOARD



General Properties and Applications

High quality abrasion resistant sheet for applications requiring tough, cut resistant stock and/or vibration absorption. Used as conveyor skirting, chute liner, blast curtains, mounting pads, chassis padding and other similar applications. Texcel's manufacturing process guarantees consistent gauge, width and quality unlike extruded products.

Technical Data

Durometer	60 +/-5
Tensile Strength	1,500
Temperature Range	-25°F to +175°F
Elongation	350%
Composition	Abrasion-resistant SBR/GUM
ASTM Call Out	D2000-M2-AA608-A13-B33-EA14

Gauge (in.)	x	Width (in.)	Part Number	Feet / Roll	Sq Yds/ Roll	Lbs / Roll (avg.)
1/8"	x	48"	SKIRT-4	50'	22.2	189
1/4"	x	48"	SKIRT-8	50'	22.2	377
3/8"	x	48"	SKIRT-12	50'	22.2	567
1/2"	x	48"	SKIRT-16	50'	22.2	755
3/4"	x	48"	SKIRT-24	50'	22.2	1,135
1"	x	48"	SKIRT-32	50'	22.2	1,512

- ① Tex-TUFF can be combined with Tex-GOLD, Tex-WIPER, Tex-BEVEL and Tex-PROTECT to achieve maximum price breaks.
- ① Combine Tex-TUFF with any other Texcel products for Prepaid Freight on shipments of \$2,000 or 2,000 lbs.

Tex-TIP:
Tex-TUFF is engineered for abrasion resistance and shock absorption, making it an ideal material for diverse industrial and manufacturing applications.

