

# Tex-WIPER

## 80 DUROMETER SKIRTBOARD



### General Properties and Applications

Slit-to-width, high abrasion resisting SBR/GUM blend used for belt wiper service, snowplow impact control and mounting pads.

Texcel's manufacturing process guarantees consistent gauge, width and quality unlike extruded products. Packaged with three binding straps to keep rolls in tact and prevent telescoping during shipping, storage and handling. Roll sizes are clearly marked for easy identification.

### Technical Data

Durometer	80 +/-5
PSI	1,740
Temperature Range	-25°F to +175°F
Elongation	350%
Composition	Abrasion-resistant SBR/GUM
ASTM Call Out	D2000-M2-AA8012-A13-B33-EA14



Gauge (in.)	x	Width (in.)	Part Number	Feet / Roll	Lbs / Roll (avg.)
1/2"	x	4"	WIPE-16-4	50'	68
1/2"	x	5"	WIPE-16-5	50'	79
1/2"	x	6"	WIPE-16-6	50'	88
1/2"	x	8"	WIPE-16-8	50'	119
3/4"	x	6"	WIPE-24-6	50'	140
3/4"	x	8"	WIPE-24-8	50'	187
1"	x	5"	WIPE-32-5	50'	153
1"	x	6"	WIPE-32-6	50'	187
1"	x	8"	WIPE-32-8	50'	249
1"	x	9"	WIPE-32-9	50'	278
1"	x	12"	WIPE-32-12	50'	374

- ① Tex-WIPER can be combined with Tex-GOLD, Tex-TUFF, Tex-BEVEL and Tex-PROTECT to achieve maximum price breaks.
- ① Combine Tex-WIPER with any other Texcel products for Prepaid Freight on shipments of \$2,000 or 2,000 lbs.

