

GAMMA™-BLEND

400psi Blender/Fracturing Hose

A rugged hose designed for blender/fracturing operations in oilfield and gas exploration applications. The abrasion-resistant cover is constructed to withstand extended exposure to harsh, abrasive conditions typically seen in oilfield fracturing operations. Designed for the transfer of 98% water and sand mixtures, oil slurries and crude oil.



TECHNICAL DATA

Tube	Black, fuel and oil-resistant, NBR compound	
Cover	Black, abrasion-resistant, SBR/Nitrile blend compound*	
Reinforcement	High tensile strength tire cord plies	
Safety Factor	4:1	
Temperature	-30°F to +180°F	
Branding	TEXCEL® GAMMA™-BLEND - BLENDER / FRACTURING DISCHARGE HOSE 400 PSI W.P.	

*Additional UHMW heavy-duty cover application available for special order.

	#				
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Lbs./Ft.
4"	GBF40S1-4.0	4-49/64"	100'/200'	400	3.02



GREEN INITIATIVES

As leaders in the industry, we feel obligated to do our part to protect our natural resources. Our sustainability efforts begin in the research and development phase and extend to creating innovative ways to recycle and reuse our products. We recycle all of our used materials, including fittings, bands and straps, and have a corporate paper recycling program.