

# BR14

## R14 Stainless Steel Braided PTFE Hose

High pressure and non-conductive PTFE tubing with 100R14 stainless steel outer braid for paints, oil, air, and water based fluids.



### TECHNICAL DATA

Specifications	Meets or Exceeds SAE 100R14
Tube	PTFE
Cover	Stainless steel outer braid
Temperature	-76°F to +500°F (-60°C to +260°C)
Fittings	FT SERIES

Dash	I.D.		# Part Number	O.D.		Working Pressure		Burst Pressure		Bend Radius		Weight	
	Inch	Dn		Inch	mm	psi	bar	psi	bar	inch	mm	lbs/ft	Kg/mt
4	¼	6	BR14-4	0.35	8.90	2,540	175	10,160	920	1.77	45	0.06	0.09
6	⅜	10	BR14-6	0.47	12.40	1,960	135	7,840	540	2.16	55	0.10	0.15
8	½	12	BR14-8	0.61	15.70	1,740	120	6,960	480	2.75	70	0.14	0.21
10	⅝	16	BR14-10	0.75	19.10	1,450	100	5,800	400	5.11	130	0.18	0.26
12	¾	19	BR14-12	0.87	22.20	1,310	90	5,240	360	7.48	190	0.22	0.32
16	1	25	BR14-16	1.15	29.30	940	65	3,760	260	10.62	270	0.31	0.45