

GAMMA™-BULK

Dry Bulk Material Discharge Hose

Soft-wall discharge hose used in the transfer of dry materials and slurries. Ideal for dry cement, pebble lime and other abrasive media.



TECHNICAL DATA

Tube	Black, abrasion-resistant NR/SBR, static-dissipating materials	
Cover	Black, abrasion-resistant NR/SBR	
Reinforcement	High tensile tire cord plies	
Safety Factor	4:1	
Temperature	-40°F to +180°F	
Branding	TEXCEL® GAMMA™-BULK - DRY CEMENT DISCHARGE HOSE STATIC CONDUCTIVE XX TUBE 75 PSI W.P.	

I.D.	Part Number	Tube Gauge	O.D.	Std. Length	Working Pressure (psi)	Number of Plies	Lbs./Ft.
4"	GBU75S1B-4-4	1/8"	4-28/64"	100'	75	2	1.72
	GBU75S1B-4-6	3/16"	4-40/64"	100'	75	2	2.20
	GBU75S1B-4-8	1/4"	4-51/64"	100'	75	2	2.61
5"	GBU75S1B-5-4	1/8"	5-30/64"	100'	75	2	2.27
	GBU75S1B-5-6	3/16"	5-40/64"	100'	75	2	2.75
	GBU75S1B-5-8	1/4"	5-51/64"	100'	75	2	3.25