



GAMMA™-BULK

Dry Bulk Material Discharge Hose



General Properties and Applications

Soft-wall discharge hose used in the transfer of dry materials and slurries. Ideal for dry cement, pebble lime and other abrasive media.

TECHNICAL DATA

Tube	Black, abrasion-resistant NR/SBR, static-dissipating materials
Cover	Black, abrasion-resistant NR/SBR
Reinforcement	High tensile tire cord plies
Safety Factor	4:1
Temperature	-40°F to +180°F
Branding	TEXCEL® GAMMA™-BULK - DRY CEMENT DISCHARGE HOSE STATIC CONDUCTIVE XX TUBE 75 PSI W.P.



I.D.	Part Number	Tube Gauge	O.D.	Std. Length	Working Pressure (psi)	Number of Plies	Lbs./Ft.
4"	GBU75S1B-4-4	1/8"	4-7/16"	100'	75	2	1.72
	GBU75S1B-4-6	3/16"	4-5/8"	100'	75	2	2.20
	GBU75S1B-4-8	1/4"	4-51/64"	100'	75	2	2.61
5"	GBU75S1B-5-4	1/8"	5-15/32"	100'	75	2	2.27
	GBU75S1B-5-6	3/16"	5-5/8"	100'	75	2	2.75
	GBU75S1B-5-8	1/4"	5-51/64"	100'	75	2	3.25