GAMMA™-FLEX TANK

Corrugated Tank Truck Hose

A world-class hose for tank truck, in-plant and oilfield loading operations requiring a strong yet flexible hose. Dramatic flexibility (one-to-one ratio, up to 4" inside diameter) for ease of handling.



TECHNICAL DATA

Tube Black, Nitrile, 55% aromatics (ORS)

Cover Black, Neoprene (flex corrugated)

Reinforcement High tensile tire cord plies; helix wire

Safety Factor 4:1

Temperature -40°F to +180°F

Branding TEXCEL® GAMMA™-FLEX TANK - FLEXIBLE TANK

TRUCK HOSE 150 PSI W.P.

Features Exceptional flexibility

10	#	O	لتنتينا	9) (Hg	ଠୁ	Ê
I.D.	Part Number	0.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
1-1/2"	GTA15F1-1.5	1-63/64"	100'/200'	150	29	1.5"	0.77
2"	GTA15F1-2.0	2-15/32"	100'/200'	150	29	2"	1.02
2-1/2"	GTA15F1-2.5	3"	100'/200'	150	29	2.5"	1.31
3"	GTA15F1-3.0	3-1/2"	100'/200'	150	29	3"	1.60
4"	GTA15F1-4.0	4-9/16"	100'/200'	150	29	4"	2.55
5"	GTA15F1-5.0	5-46/64"	100'	150	29	6"	3.86
6"	GTA15F1-6.0	6-3/4"	20'/100'	150	25	8"	4.17
8"	GTA15C1-8.0	8-13/16"	100'	150	25	10"	6.02





