

TEX-FLO 4HD

Heavy-Duty 4-Ply Water Discharge Hose

Soft-wall design gives similar performance to a lay-flat hose, but with increased abrasion resistance and tensile strength. FLO-HD is made of a premium-quality SBR/EPDM blend for maximum weather resistance and life in abusive service.



TECHNICAL DATA

Tube	Black, SBR/EPDM blend	
Cover	Black, SBR/EPDM blend	
Reinforcement	High tensile tire cord plies	
Safety Factor	3:1	
Temperature	-40°F to +180°F	
Branding	TEXCEL® TEX-FLO 4HD - HEAVY DUTY WATER DISCHARGE HOSE 4PLY XXXPSI WP	

I.D.	Part Number	O.D.	Std. Length	Fabric Plies	Working Pressure (psi)	Lbs./Ft.
1-1/2"	FLO-4HD-1.5	1-58/64"	100'	4	250	0.56
2"	FLO-4HD-2.0	2-26/64"	100'	4	250	0.73
2-1/2"	FLO-4HD-2.5	2-58/64"	100'	4	250	0.88
3"	FLO-4HD-3.0	3-26/64"	100'	4	250	1.04
4"	FLO-4HD-4.0	4-27/64"	100'	4	200	1.41
4-1/2"	FLO-4HD-4.5	4-59/64"	100'	4	200	1.58
5"	FLO-4HD-5.0	5-28/64"	100'	4	200	1.89
6"	FLO-4HD-6.0	6-29/64"	100'	4	200	2.48
8"	FLO-4HD-8.0	8-30/64"	100'	4	200	3.39
10"	FLO-4HD-10.0	10-34/64"	100'	4	150	4.44
12"	FLO-4HD-12.0	12-34/64"	50'	4	150	5.30