

TEX-GS

General Service Air & Water Hose

A tough, heavy-duty, abrasion and ozone-resistant general service hose. Designed for the transfer of air, mild chemicals and water across multiple applications. The ability to order this product in continuous lengths provides efficiently in inventory controls as well as ease of handling at job sites.



On 1/2" – 1" sizes that cannot be made to 600', but are ordered at 600', we will produce 2 – 300' lengths. 1-1/4" X 300' Reels will be made using 2- 150' lengths. 1-1/2" x 250' Reels will be made using a 100' length + a 150' length. There will be no more than 3 pieces per reel and there will never be a piece that is shorter than 50'

TECHNICAL DATA

Tube	Black, EPDM
Cover	Red, SBR/EPDM
Reinforcement	One or two braided polyester cords
Safety Factor	3:1
Temperature	-20°F to +180°F
Branding	TEXCEL® TEX-GS - GENERAL SERVICE AIR AND WATER -<ID>-XXXPSI WP-LOT (white letters)
Packaging	Coils are continuous lengths

I.D.	Package Type	# Part Number	O.D.	Std. Length	Working Pressure (psi)	Lbs./Ft.
1/4"	Reel	GS-4-R250-600R	33/64"	600'	250	0.12
	Coil	GS-4-C250-200R	33/64"	200'	250	0.12
5/16"	Reel	GS-5-R250-600R	38/64"	600'	250	0.15
3/8"	Reel	GS-6-R250-600R	43/64"	600'	250	0.19
	Coil	GS-6-C250-200R	43/64"	200'	250	0.19
1/2"	Reel	GS-8-R250-600R	53/64"	600'	250	0.26
	Coil	GS-8-C250-200R	53/64"	200'	250	0.26
5/8"	Reel	GS-10-R250-600R	63/64"	600'	250	0.33
	Reel	GS-12-R250-600R	1-9/64"	600'	250	0.45
3/4"	Coil	GS-12-C250-50R	1-9/64"	50'	250	0.45
	Coil	GS-12-C250-200R	1-9/64"	200'	250	0.45
1"	Reel	GS-16-R250-400R	1-27/64"	400'	250	0.60
	Coil	GS-16-C250-50R	1-27/64"	50'	250	0.60
1-1/4"	Reel	GS-20-R250-300R	1-47/64"	300'	250	0.86
1-1/2"	Reel	GS-24-R250-250R	2-8/64"	250'	250	1.37
2"	Reel	GS-32-R250-200R	2-38/64"	200'	250	1.61