

HS5KXT TERA-GLIDE XT

5,000 PSI Spiral Isobaric Extreme Abrasion Resistant Hose

Very high pressure compact four and six spiral extreme abrasion resistance hydraulic hose. HS5KXT provides exceptional flexibility, rated to 1 million cycles at ½ minimum bend radius compared to SAE or DIN hoses.



TECHNICAL DATA

Specifications	Meets or Exceeds SAE 100R13, ISO 18752 DC
Tube	Black, oil resistant synthetic rubber
Reinforcement	4 high tensile steel wire spirals
Cover	TERA-GLIDE XT: Black, extreme abrasion resistant, synthetic rubber with UHMWPE. Resistant to oil, ozone and to UV rays.
Temperature	-40°F to +250°F (-40°C to +121°C)
Industry Approvals	MSHA, ABS, DNV, USCG
Fittings	F4 SERIES



Dash	I.D.		Part Number	O.D.		Working Pressure		Burst Pressure		Bend Radius		Weight	
	Inch	Dn		Inch	mm	psi	bar	psi	bar	inch	mm	lbs/ft	Kg/mt
12	¾	19	HS5KXT-12	1.19	30.1	5,500	380	22,000	1,520	4.70	120	0.81	1.20
16	1	25	HS5KXT-16	1.47	37.4	5,100	350	20,400	1,400	5.90	150	1.21	1.80