


GAMMA™-HTA









Hot Tar and Asphalt Hose

This rugged hose is specifically designed for the transfer of petroleum-based products such as high temperature asphalt, tar, and hot oils. Suitable for suction and discharge service on rail transport cars, tank trucks, bulk stations, storage tanks and disposing units.



TECHNICAL DATA

Tube	Black, special synthetic acrylic rubber, heat and abrasion resistant	
Cover	Black, CR anti-static, with a smooth abrasion, weather and heat resistant wrapped cover	
Reinforcement	High tensile tire cord plies; dual helix wire	
Safety Factor	4:1	
Temperature	-20°F to +350°F (intermittent)	
Branding	TEXCEL® GAMMA™-HTA - HOT TAR & ASPHALT HOSE 150 PSI W.P.	
Safety Note	<p>Texcel recommends using Dixon Valve and Coupling's Boss™ 4-Bolt Clamp System for Hot Tar and Asphalt hose. Please consult Dixon's selection and installation recommendations, including bolt re-tightening procedures, to insure proper hose assembly.</p> <p>Maximum service temp. 350°F, intermittent use only</p>	

							
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
2"	GHTA15S1-2.0	2- ⁴⁶ / ₆₄ "	100'/200'	150	29	10"	1.80
3"	GHTA15S1-3.0	3- ⁵⁰ / ₆₄ "	100'/200'	150	29	15"	2.94
4"	GHTA15S1-4.0	4- ⁵¹ / ₆₄ "	100'/200'	150	29	20"	3.89