

TEX-MOR

Moderate Oil Resistant Sheet



General Properties and Applications

Commercial-grade sheet rubber used for a wide variety of gasket, sealing, cushioning and weather-stripping applications where medium oil resistance is required. Our exclusive post-cure process provides a smooth and clean finish that is free of talc, a must for PSA applications.

TECHNICAL DATA

Durometer	60 +/-5
Color	Black
Temperature	-20°F to +190°F
Tensile Strength	600 psi
Elongation	250%
Specifications	ASTM D2000 M1-BC604



Width	Gauge	Part Number	Ln. Ft./Roll	Sq. Yds./Roll	Lbs./Roll
36"	1/16"	MOR-2-36	50'	16.7	71
	3/32"	MOR-3-36	50'	16.7	106
	1/8"	MOR-4-36	50'	16.7	142
	3/16"	MOR-6-36	50'	16.7	213
	1/4"	MOR-8-36	50'	16.7	284
	3/8"	MOR-12-36	50'	16.7	426
	1/2"	MOR-16-36	50'	16.7	568
	3/4"	MOR-24-36	30'	10	511
48"	1"	MOR-32-36	30'	10	681
	1/16"	MOR-2-48	50'	22.2	95
	1/8"	MOR-4-48	50'	22.2	189
	3/16"	MOR-6-48	50'	22.2	284
	1/4"	MOR-8-48	50'	22.2	378
	3/8"	MOR-12-48	50'	22.2	568
	1/2"	MOR-16-48	50'	22.2	757
	3/4"	MOR-24-48	30'	13.3	681
1"	MOR-32-48	30'	13.3	908	