



*Mandals **Mantex** is a flexible, yet tough and lightweight hose designed for compressed air applications.*

The hose can also be used to transport a wide range of liquids, from sewage to snow production.

APPLICATIONS

- COMPRESSED AIR
- WITHSTANDS HIGHER WORKING PRESSURES

DESIGN

- Made from a blend of nitrile rubber with added UV barrier to prevent damage from UV radiation
- A strong weave completely embedded in the nitrile rubber provides solid construction

FEATURES

- Lightweight construction combined with higher pressure ratings
- High-strength, added UV barrier, high quality materials and excellent adhesion between weave and outer rubber layer gives the hose a long life expectancy.

ADVANTAGE

- Field-proven hose
- Max temperature up to +230F
- Coils easily for storage and transportation

ID	PART	WALL THICKNESS		WEIGHT		BURST PRESSURE		TENSILE STRENGTH	
		Inch	mm	Lbs / ft	Kg / m	Psi	Bar	X1000 lbs	Tons
¾	MANTEX-.75-50	0.09	2.3	0.14	0.21	1450	100	4.2	1.9
¾	MANTEX-.75-100	0.09	2.3	0.14	0.21	1450	100	4.2	1.9
1	MANTEX-1.0-50	0.10	2.5	0.18	0.27	1450	100	5.1	2.3
1	MANTEX-1.0-100	0.10	2.5	0.18	0.27	1450	100	5.1	2.3
1 ½	MANTEX-1.5-100	0.10	2.5	0.25	0.38	1235	85	7.7	3.5
2	MANTEX-2.0-100	0.10	2.5	0.35	0.53	870	60	10.4	4.7
2 ½	MANTEX-2.5-100	0.11	2.9	0.45	0.68	725	50	14.8	6.7
3	MANTEX-3.0-100	0.12	3.1	0.63	0.95	725	50	17.9	8.1

NOTE: SAFETY BP/WP IS 2:1 (50%). FOR ALL NON-HAZARD AND/OR NON-FLAMMABLE LIQUIDS.

NOTE: SAFETY FACTOR SF 1:4.

mandals
SINCE 1775

SOLD TO YOU
IN THE USA BY

TEXCEL

While we have made every attempt to ensure that the information contained in this brochure is accurate, neither Mandals nor Texcel is responsible for any errors or omissions, or for the results obtained from the use of this information. Mandals and Texcel reserve the right to modify any specifications without prior notice to meet or exceed changing standards. For special diameters, features and construction characteristics please contact us at layflat.hose@texcelrubber.com