

MANTEX HP



Please contact us for more info:

800.231.7116

layflat.hose@texcelrubber.com

Mandals **Mantex HP** is a compressed air hose designed to withstand higher working pressures, while offering a lightweight solution with ease of deployment and storage.



APPLICATIONS

- COMPRESSED AIR
- WITHSTANDS HIGHER WORKING PRESSURES

DESIGN

- Double jacket hose solution ensures high burst pressure, puncture resistance and flexibility
- High tensile polyester weaves covered and lined with an ultimate abrasion-resistant and oil-resistant thermoplastic polyurethane (TPU)

FEATURES

- Light, yet rugged and hardwearing hose
- The low weight, combined with a high pressure rating, makes the hose popular and easy to use
- The hose does not stretch when pulled and has a very high pressure rating versus wall thickness
- Excellent abrasion resistance
- Double Jacket hose with TPU outer layer / inner layer covered with EPDM rubber

ADVANTAGE

- Field-proven hose
- High working pressure of 635 PSI
- High Flexibility
- Coils easily for storage and transportation
- Max temperature up to +230F

ID	PART	WALL THICKNESS		WEIGHT		BURST PRESSURE		TENSILE STRENGTH	
		Inch	mm	Lbs / ft	Kg / m	Psi	Bar	X1000 lbs	Tons
2	MANTEXHP-2.0-50	0.17	4.4	0.55	0.82	2535	175	31.7	14.3
2	MANTEXHP-2.0-100	0.17	4.4	0.55	0.82	2535	175	31.7	14.3
3	MANTEXHP-3.0-50	0.18	4.5	0.83	1.24	1740	110	46.6	21
3	MANTEXHP-3.0-100	0.18	4.5	0.83	1.24	1740	110	46.6	21

NOTE: SAFETY BP/WP IS 2:1 (50%). FOR ALL NON-HAZARD AND/OR NON-FLAMMABLE LIQUIDS.

NOTE: SAFETY FACTOR BP/WP IS 4:1 (25%) FOR COMPRESSED AIR. (ISO 7751:1991)

mandals
SINCE 1775

SOLD TO YOU
IN THE USA BY



While we have made every attempt to ensure that the information contained in this brochure is accurate, neither Mandals nor Texcel is responsible for any errors or omissions, or for the results obtained from the use of this information. Mandals and Texcel reserve the right to modify any specifications without prior notice to meet or exceed changing standards. For special diameters, features and construction characteristics please contact us at layflat.hose@texcelrubber.com