



# GAMMA™-MULTI OIL

## 500psi Multi-Purpose Discharge Hose








This heavy-duty discharge hose can be used in a variety of applications in severe conditions such as oil waste, drilling muds, high pressure water or fracturing.



### TECHNICAL DATA

Tube	Black, fuel and oil-resistant, NBR compound
Cover	Black, oil, weather and abrasion-resistant NR/SBR compound
Reinforcement	High tensile tire cord plies; static wire
Safety Factor	4:1
Temperature	-30°F to +180°F
Branding	TEXCEL® GAMMA™-MULTI OIL - MULTIPURPOSE DISCHARGE HOSE 500 PSI W.P.



						
I.D.	Part Number	O.D.	Std. Length	Plies	Working Pressure (psi)	Lbs./Ft.
2"	GMO50S1-2.0	2- <sup>36</sup> / <sub>64</sub> "	100'/200'	4	500	1.22
3"	GMO50S1-3.0	3- <sup>43</sup> / <sub>64</sub> "	100'/200'	6	500	2.15
4"	GMO50S1-4.0	4- <sup>50</sup> / <sub>64</sub> "	100'/200'	8	500	3.31
5"	GMO50S1-5.0	5- <sup>52</sup> / <sub>64</sub> "	100'/200'	8	500	4.97