



TEX-OSD 250

250psi Oil Suction & Discharge Hose









Smooth bore dock hose with high strength construction and 250psi working pressure for the longest possible service life under severe conditions. Meets U.S.C.G. certification requirements when assembled per USCG 33CFR 154.500 specifications.



TECHNICAL DATA

Tube	Black, Nitrile, 55% aromatics (ORS)
Cover	Black, Neoprene
Reinforcement	High tensile tire cord plies; dual helix on sizes 2"-4"; single helix wire on sizes 6"-12"
Safety Factor	4:1
Temperature	-40°F to +190°F
Branding	TEXCEL® TEX-OSD 250 - OIL SUCTION AND DISCHARGE HOSE 250 PSI W.P. MEETS USCG 33CFR 154.500
Specifications	Meets U.S.C.G. requirements



							
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
2"	OSD-2.0	2- ⁶⁰ / ₆₄ "	100'	250	29	8"	2.15
3"	OSD-3.0	4- ¹⁶ / ₆₄ "	100'	250	29	11"	3.41
4"	OSD-4.0	5- ²⁰ / ₆₄ "	100'	250	29	15"	4.87
6"	OSD-6.0	7- ²⁴ / ₆₄ "	100'	250	29	25"	8.18
8"	OSD-8.0	9- ⁴⁸ / ₆₄ "	100'	250	29	31"	14.35
10"	OSD-10.0	12"	40'	250	29	36"	20.49
12"	OSD-12.0	14- ⁸ / ₆₄ "	40'	250	29	40"	26.49