

# SIGMA-ULTRAVAC-SBR™









## SBR Vacuum Hose

Ultravac SBR™ is a specially compounded vacuum hose that is suitable for use in a multitude of wet and dry material applications. Being lightweight and flexible, Ultravac SBR™ is the ideal hose for vacuum trucks, hydro-excavators, and sewer cleaning equipment. Its static dissipative carbon black tube makes it suitable for handling sand, gravel, dry cement, iron chips, grains and other light abrasives.



### TECHNICAL DATA

Construction	Static dissipating, SBR blended tube with a rigid right-handed PVC helix
Safety Factor	3:1
Temperature	-40°F to +158°F
Branding	SIGMA SERIES - ULTRAVAC SBR-<ID>-LOT
Compared To	180 AR
Features	Excellent flexibility when compared to PVC/polyurethane hose

							
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum in./HG	Bend Radius	Lbs./Ft.
1 ½"	SP-SBR-1.5	1.82"	100'	45	29	2"	0.35
2"	SP-SBR-2.0	2.35"	100'	40	29	3"	0.52
2 ½"	SP-SBR-2.5	2.95"	100'	35	29	3"	0.90
3"	SP-SBR-3.0	3.5"	100'	35	29	3"	1.08
4"	SP-SBR-4.0	4.63"	50', 100'	30	29	5"	1.80
5"	SP-SBR-5.0	5.76"	50', 100'	30	28	5"	2.45
6"	SP-SBR-6.0	6.73"	50', 100'	30	28	9"	3.05
8"	SP-SBR-8.0	9.04"	50'	30	27	15"	5.63