

GAMMA™ - PUMP

Oil Suction & Discharge Hose with Built-In Flanges

This smooth bore OS & D hose is manufactured with built-in carbon steel 150# ANSI flanges. Meets U.S.C.G. certification requirements per USCG 33CFR 154.500.



TECHNICAL DATA

Tube	Black, Nitrile, 55% aromatics (ORS)
Cover	Black, Neoprene
Reinforcement	High tensile tire cord plies; helix wire
Safety Factor	4:1
Temperature	-40°F to +190°F
Ends	ANSI 150# carbon steel built-in fixed by floating flanges
Branding	TEXCEL® GAMMA™ PUMP 250 - OIL SUCTION AND DISCHARGE HOSE 250 PSI W.P. MEETS USCG 33CFR 154.500
Specifications	Meets U.S.C.G. requirements

ANSI Flanges	Assembly Dimensions	# Part Number	O.D.	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Assembly
Built-In Fixed x Floating Flanged Assemblies	4" x 20'	PMP-4-20-FL	4- ⁵⁹ / ₆₄ "	250	29	23 ⁵ / ₈ "	115
	6" x 20'	PMP-6-20-FL	7- ³ / ₃₂ "	250	29	31 ¹ / ₂ "	190
	8" x 20'	PMP-8-20-FL	9- ¹ / ₄ "	250	29	39 ³ / ₈ "	305
	10" x 20'	PMP-10-20-FL	11 ¹¹ / ₃₂ "	250	29	59 ¹ / ₁₆ "	450
	12" x 20'	PMP-12-20-FL	13- ⁵ / ₁₆ "	250	29	70 ⁵⁵ / ₆₄ "	550