

SIGMA-URE-B™









Polyurethane Material Handling Hose with PVC Cover

Abrasion-resistant, polyurethane tube for material handling in dry applications, such as sandblast recovery lines, roof rock cleaning and other abrasive applications. Made of static-dissipating material that remains flexible at low temperatures for ease of handling.



TECHNICAL DATA

| | |
|---------------|---|
| Construction | Black, flexible PVC and smooth with black, rigid, right-handed helix and smooth, polyurethane liner |
| Safety Factor | 3:1 |
| Temperature | -40°F to +150°F |
| Compared To | UBK |
| Safety Note | Service temperature depends on actual application |

|  I.D. |  Part Number |  O.D. |  Std. Length |  Working Pressure (psi) |  Vacuum (in./HG) |  Bend Radius |  Lbs./Ft. |
|--|---|--|---|--|---|---|--|
| 2" | SPVC-URE-B-2.0 | 2.40" | 50'/100' | 40 | 29 | 2" | 0.51 |
| 2-1/2" | SPVC-URE-B-2.5 | 3.10" | 50'/100' | 40 | 29 | 4" | 0.77 |
| 3" | SPVC-URE-B-3.0 | 3.55" | 50'/100' | 40 | 29 | 4" | 0.87 |
| 4" | SPVC-URE-B-4.0 | 4.68" | 50'/100' | 35 | 29 | 6" | 1.55 |
| 5" | SPVC-URE-B-5.0 | 5.71" | 50'/100' | 30 | 28 | 10" | 2.30 |
| 6" | SPVC-URE-B-6.0 | 7.05" | 20'/50'/100' | 30 | 28 | 12" | 3.40 |
| 8" | SPVC-URE-B-8.0 | 9.05" | 20'/50' | 30 | 28 | 15" | 4.88 |