

GAMMA™-TANK









Tank Truck Hose

The industry standard for tank truck, in-plant and oilfield loading operations requiring a strong yet flexible hose.



TECHNICAL DATA

Tube	Black, Nitrile, 55% aromatics (ORS)	
Cover	Black, Neoprene (smooth)	
Reinforcement	High tensile tire cord plies; dual helix wire	
Safety Factor	4:1	
Temperature	-40°F to +180°F	
Branding	TEXCEL® GAMMA™-TANK - TANK TRUCK HOSE 150 PSI W.P.	

							
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
1-¼"	GTA15S1-125	1- ⁴³ / ₆₄ "	100'/200'	150	29	4"	0.70
1-½"	GTA15S1-1.5	1- ⁵⁹ / ₆₄ "	100'/200'	150	29	6"	0.84
2"	GTA15S1-2.0	2- ²⁹ / ₆₄ "	100'/200'	150	29	8"	1.10
2-½"	GTA15S1-2.5	2- ⁶¹ / ₆₄ "	100'/200'	150	29	10"	1.48
3"	GTA15S1-3.0	3- ³² / ₆₄ "	100'/200'	150	29	13"	1.79
4"	GTA15S1-4.0	4- ³⁶ / ₆₄ "	100'/200'	150	29	19"	2.64