



TANK TRUCK HOSE 150PSI



The industry standard for tank truck, in-plant, and oilfield loading operations requiring a strong yet flexible hose. Suitable for the transfer of gasoline, oil, ethanol blends and other petroleum-base products up to 50% aromatic content. Designed for pressure, gravity flow, or full suction service.

- TUBE:** Black, Nitrile, 55% aromatics (ORS)
- COVER:** Black, Neoprene (smooth)
- REINFORCEMENT:** High tensile tire cord plies; dual helix wire
- SAFETY FACTOR:** 4:1
- TEMPERATURE:** -40°F to +180°F
- BRANDING:** RAGCO TANK TRUCK HOSE 150PSI WP

ID	PART NUMBER	OD	WORKING PRESSURE (PSI)	VACUUM RATING (IN/HG)	BEND RADIUS	LBS/FT
1"	R-TTH100-150	1 29/64"	150	29	3"	.43
1 1/2"	R-TTH150-150	1 59/64"	150	29	6"	.84
2"	R-TTH200-150	2 29/64"	150	29	8"	1.10
3"	R-TTH300-150	3 32/64"	150	29	13"	1.79
4"	R-TTH400-150	4 36/64"	150	29	19"	2.64
* 6"	R-TTHC600-150	6 48/64"	150	25	8"	4.17

*6" SIZE PROVIDED WITH CORRUGATED COVER



RAGCO

RAGCO.COM 800.543.9265

Contact Ragco to find the affiliate to serve your industrial hose needs.