

# TEX-WIPER

Belt Wiper 80 Duro






## General Properties and Applications

Slit-to-width, high abrasion-resistant SBR/GUM blend used for belt wiper service, impact control and mounting pads. Texcel's manufacturing process guarantees consistent gauge, width and quality, unlike extruded products. Packaged with three binding straps to keep rolls intact and prevent telescoping during shipping, storage and handling. Roll sizes are clearly marked for easy identification.

## TECHNICAL DATA

Durometer	80 +/-5
Temperature	-25°F to +175°F
Tensile Strength	1,740 psi
Composition	Abrasion-resistant SBR/GUM
Elongation	300%



 Width	 Gauge	 Part Number	 Ft./Roll	 Lbs./Roll (avg.)
4"	1/2"	WIPE-16-4	50'	68
5"	1/2"	WIPE-16-5	50'	79
6"	1/2"	WIPE-16-6	50'	88
8"	1/2"	WIPE-16-8	50'	119
6"	3/4"	WIPE-24-6	50'	140
8"	3/4"	WIPE-24-8	50'	187
5"	1"	WIPE-32-5	50'	153
6"	1"	WIPE-32-6	50'	187
8"	1"	WIPE-32-8	50'	249
9"	1"	WIPE-32-9	50'	278
12"	1"	WIPE-32-12	50'	374